

User Manual



TDS 500D, TDS 600B & TDS 700D Digitizing Oscilloscopes

071-0130-00

This document applies for firmware version 1.0
and above.

Table of Contents

General Safety Summary	ix
Preface	xi
Related Manuals	xi
Default Model	xii
Model References	xii
Conventions	xii

Getting Started

Product Description	1-1
Differences by Model	1-3
Product Specification	1-4
Start Up	1-5
Preparation	1-5
Putting into Service	1-6

Operating Basics

Overview	2-1
Operating Interface Maps	2-3
Tutorial	2-9
Setting Up for the Examples	2-9
Example 1: Displaying a Waveform	2-13
Example 2: Displaying Multiple Waveforms	2-17
Example 3: Taking Automated Measurements	2-22
Example 4: Saving Setups	2-28

Reference

Overview	3-1
Acquiring and Displaying Waveforms	3-5
Coupling Waveforms to the Oscilloscope	3-5
Setting up Automatically: Autoset and Reset	3-9
Selecting Channels	3-12
Scaling and Positioning Waveforms	3-15
Choosing an Acquisition Mode	3-27
Customizing the Display	3-40
Customizing the Display Color	3-47
Zooming on Waveforms	3-53
Using DPO Acquisition Mode	3-59
Using FastFrame [™]	3-67
Triggering on Waveforms	3-73
Triggering Concepts	3-73
Triggering from the Front Panel	3-78
Triggering on a Waveform Edge	3-82
Triggering Based on Logic	3-86

Triggering on Pulses	3-99
Communications Triggering	3-113
Delayed Triggering	3-117
Measuring Waveforms	3-125
Taking Automated Measurements	3-126
Taking Cursor Measurements	3-138
Taking Graticule Measurements	3-144
Displaying Histograms (TDS 500D and TDS 700D Models Only)	3-145
Mask Testing (Option 2C Only)	3-148
Optimizing Measurement Accuracy: SPC and Probe Cal	3-156
Saving Waveforms and Setups	3-165
Saving and Recalling Setups	3-165
Saving and Recalling Waveforms and Acquisitions	3-168
Managing the File System	3-175
Printing a Hardcopy	3-180
Communicating with Remote Instruments	3-191
Determining Status and Accessing Help	3-197
Displaying Status	3-197
Displaying the Banner	3-199
Displaying Help	3-199
Using Features for Advanced Applications	3-201
Limit Testing	3-201
Waveform Math	3-206
Fast Fourier Transforms	3-209
Waveform Differentiation	3-228
Waveform Integration	3-233

Appendices

Appendix A: Options and Accessories	A-1
Appendix B: Algorithms	B-1
Appendix C: Packaging for Shipment	C-1
Appendix D: Probe Selection	D-1
Appendix E: Inspection and Cleaning	E-1
Appendix F: Programmer Disk	F-1

Glossary

Index

List of Figures

Figure 1-1: Rear Panel Controls Used in Start Up	1-7
Figure 1-2: ON/STBY Button	1-8
Figure 2-1: Connecting a Probe for the Examples (P6245 shown) ..	2-10
Figure 2-2: SETUP Button Location	2-11
Figure 2-3: The Setup Menu	2-11
Figure 2-4: Trigger Controls	2-12
Figure 2-5: The Display After Factory Initialization	2-13
Figure 2-6: The VERTICAL and HORIZONTAL Controls	2-14
Figure 2-7: TRIGGER Controls	2-15
Figure 2-8: AUTOSET Button Location	2-16
Figure 2-9: The Display After Pressing Autoset	2-16
Figure 2-10: Display Signals Requiring Probe Compensation	2-17
Figure 2-11: The Channel Buttons and Lights	2-18
Figure 2-12: The Vertical Main Menu and Coupling Side Menu	2-20
Figure 2-13: The Menus After Changing Channels	2-21
Figure 2-14: Measure Main Menu and Select Measurement Side Menu	2-23
Figure 2-15: Four Simultaneous Measurement Readouts	2-24
Figure 2-16: General Purpose Knob Indicators	2-26
Figure 2-17: Snapshot of Channel 1	2-28
Figure 2-18: Save/Recall Setup Menu	2-30
Figure 3-1: How Probe Compensation Affects Signals	3-6
Figure 3-2: P6139A Probe Adjustment	3-7
Figure 3-3: The Channel Readout	3-13
Figure 3-4: Waveform Selection Priority	3-14
Figure 3-5: Scaling and Positioning	3-16
Figure 3-6: Vertical Readouts and Channel Menu	3-17
Figure 3-7: Record View and Time Base Readouts	3-20
Figure 3-8: Horizontal Controls	3-21
Figure 3-9: Displaying an Extended Acquisition Length Record ...	3-24
Figure 3-10: Extended Acquisition Length and Zoom	3-26
Figure 3-11: Acquisition: Input Analog Signal, Sample, and Digitize	3-27
Figure 3-12: Several Points May be Acquired for Each Point Used .	3-28
Figure 3-13: Real-Time Sampling	3-28

Figure 3-14: Equivalent-Time Sampling	3-29
Figure 3-15: How the Acquisition Modes Work	3-33
Figure 3-16: Acquisition Menu and Readout	3-35
Figure 3-17: Acquire Menu — Stop After	3-38
Figure 3-18: Aliasing	3-39
Figure 3-19: Display Menu — Style	3-42
Figure 3-20: Trigger Point and Level Indicators	3-43
Figure 3-21: Display Menu — Setting	3-47
Figure 3-22: Display Menu — Palette Colors	3-49
Figure 3-23: Display Menu — Map Reference Colors	3-51
Figure 3-24: Display Menu — Restore Colors	3-52
Figure 3-25: Zoom Mode with Horizontal Lock Set to None	3-56
Figure 3-26: Dual Window (Preview) Mode	3-57
Figure 3-27: Dual Zoom — Shown Dual Window (Preview) Mode ..	3-59
Figure 3-28: Normal DSO Acquisition and Display Mode Versus DPO Mode	3-61
Figure 3-29: DPO Display	3-62
Figure 3-30: Normal DSO Display	3-62
Figure 3-31: DPO XY Display	3-65
Figure 3-32: Fast Frame	3-67
Figure 3-33: Horizontal Menu — FastFrame Setup	3-68
Figure 3-34: Horizontal Menu — FastFrame Snapshot	3-70
Figure 3-35: FastFrame TimeStamp	3-71
Figure 3-36: Triggered Versus Untriggered Displays	3-74
Figure 3-37: Trigger Holdoff Time Ensures Valid Triggering	3-77
Figure 3-38: Slope and Level Controls Help Define the Trigger	3-78
Figure 3-39: TRIGGER Controls and Status Lights	3-79
Figure 3-40: Example Trigger Readouts — Edge Trigger Selected ..	3-81
Figure 3-41: Record View, Trigger Position, and Trigger Level Bar Readouts	3-82
Figure 3-42: Edge Trigger Readouts	3-83
Figure 3-43: Main Trigger Menu — Edge Type	3-83
Figure 3-44: Violation Zones for Setup/Hold Triggering	3-90
Figure 3-45: Logic Trigger Readouts — State Class Selected	3-91
Figure 3-46: Logic Trigger Menu	3-92
Figure 3-47: Logic Trigger Menu — Time Qualified TRUE	3-94
Figure 3-48: Triggering on a Setup/Hold Time Violation	3-98
Figure 3-49: Pulse Trigger Readouts	3-100
Figure 3-50: Main Trigger Menu — Glitch Class	3-102

Figure 3-51: Main Trigger Menu — Runt Class	3-105
Figure 3-52: Main Trigger Menu — Slew Rate Class	3-110
Figure 3-53: Main Trigger Menu — Comm Type	3-115
Figure 3-54: Delayed Runs After Main	3-117
Figure 3-55: Delayed Triggerable	3-118
Figure 3-56: How the Delayed Triggers Work	3-120
Figure 3-57: Delayed Trigger Menu	3-122
Figure 3-58: Histogram, Graticule, Cursor and Automated Measurements	3-125
Figure 3-59: Measurement Readouts with Statistics	3-129
Figure 3-60: Measure Menu	3-130
Figure 3-61: Measure Menu — Gating	3-131
Figure 3-62: Measure Menu — Reference Levels	3-133
Figure 3-63: Measure Delay Menu — Delay To	3-134
Figure 3-64: Snapshot Menu and Readout	3-136
Figure 3-65: Cursor Types	3-139
Figure 3-66: Cursor Modes	3-140
Figure 3-67: H Bars Cursor Menu and Readouts	3-141
Figure 3-68: Paired Cursor Menu and Readouts	3-142
Figure 3-69: Histogram Menu and Vertical Histogram	3-145
Figure 3-70: Mask menu	3-149
Figure 3-71: Creating a User Mask	3-154
Figure 3-72: Performing a Signal Path Compensation	3-157
Figure 3-73: Probe Cal Menu and Gain Compensation Display	3-160
Figure 3-74: Re-use Probe Calibration Data Menu	3-163
Figure 3-75: Save/Recall Setup Menu	3-166
Figure 3-76: Save Waveform Menu	3-170
Figure 3-77: More Menu	3-173
Figure 3-78: File Utilities	3-176
Figure 3-79: File System — Labeling Menu	3-177
Figure 3-80: Utility Menu — System I/O	3-182
Figure 3-81: Hardcopy Formats	3-183
Figure 3-82: Date and Time Display	3-185
Figure 3-83: Connecting the Oscilloscope Directly to the Hardcopy Device	3-186
Figure 3-84: Connecting the Oscilloscope and Hardcopy Device Via a PC	3-189
Figure 3-85: Typical GPIB Network Configuration	3-192
Figure 3-86: Stacking GPIB Connectors	3-193

Figure 3-87: Connecting the Oscilloscope to a Controller	3-193
Figure 3-88: Utility Menu	3-195
Figure 3-89: Status Menu — System	3-198
Figure 3-90: Banner Display	3-199
Figure 3-91: Initial Help Screen	3-200
Figure 3-92: Comparing a Waveform to a Limit Template	3-202
Figure 3-93: Acquire Menu — Create Limit Test Template	3-203
Figure 3-94: More Menu	3-207
Figure 3-95: Dual Waveform Math Main and Side Menus	3-208
Figure 3-96: System Response to an Impulse	3-211
Figure 3-97: Define FFT Waveform Menu	3-212
Figure 3-98: FFT Math Waveform in Math1	3-214
Figure 3-99: Cursor Measurement of an FFT Waveform	3-215
Figure 3-100: Waveform Record vs. FFT Time Domain Record	3-217
Figure 3-101: FFT Time Domain Record vs. FFT Frequency Domain Record	3-218
Figure 3-102: How Aliased Frequencies Appear in an FFT	3-222
Figure 3-103: Windowing the FFT Time Domain Record	3-225
Figure 3-104: FFT Windows and Bandpass Characteristics	3-228
Figure 3-105: Derivative Math Waveform	3-230
Figure 3-106: Peak-Peak Amplitude Measurement of a Derivative Waveform	3-231
Figure 3-107: Integral Math Waveform	3-235
Figure 3-108: H Bars Cursors Measure an Integral Math Waveform	3-236
Figure B-1: MCross Calculations	B-4
Figure B-2: Fall Time	B-9
Figure B-3: Rise Time	B-14
Figure B-4: Choosing Minima or Maxima to Use for Envelope Measurements	B-16
Figure D-1: Typical High Voltage Probes	D-3
Figure D-2: A6303 Current Probe Used in the AM 503S Opt. 03 ...	D-5
Figure F-1: Equipment Needed to Run the Example Programs	F-1

List of Tables

Table 1-1: Key Features and differences of models	1-3
Table 1-2: Fuse and fuse cap part numbers	1-7
Table 3-1: Autoset defaults	3-10
Table 3-2: How interleaving affects sample rate	3-31
Table 3-3: Additional resolution bits	3-34
Table 3-4: TDS 500D and TDS 700D Sampling mode selection (when fit to screen is off)	3-37
Table 3-5: XY Format pairs	3-46
Table 3-6: DPO XY Format pairs	3-65
Table 3-7: Pattern and State Logic	3-88
Table 3-8: Pulse trigger definitions	3-100
Table 3-9: Comm triggers	3-113
Table 3-10: Communications pulse forms	3-116
Table 3-11: Measurement definitions	3-126
Table 3-12: Measurement definitions	3-147
Table 3-13: Standard masks	3-155
Table 3-14: Probe cal status	3-164
Table A-1: Options	A-1
Table A-2: Standard accessories	A-4
Table A-3: Optional accessories	A-5
Table A-4: Recommended Probe Cross Reference	A-6
Table A-5: Accessory software	A-9
Table E-1: External inspection check list	E-2