

Table of Contents

General Safety Summary	v
Preface	ix
Contacting Tektronix	x

Performance Verification Procedures

Performance Verification Procedures	1-1
Input Channels vs. Model	1-2
Conventions	1-2
Brief Procedures	1-5
Self Tests	1-5
Functional Tests	1-7
Performance Tests	1-15
Prerequisites	1-15
Equipment Required	1-16
TDS 600B Test Record	1-18
TDS 500D/700D Test Record	1-22
TDS 794D Test Record	1-26
Signal Acquisition System Checks	1-29
Time Base System Checks	1-46
Trigger System Checks	1-49
Output Signal Checks	1-62
Option 05 Video Trigger Checks (Not Available on TDS 794D)	1-71
Sine Wave Generator Leveling Procedure	1-88
Optical Filters Checks (TDS 500D/TDS 700D Only)	1-91

Specifications

Specifications	2-1
Product Description	2-1
User Interface	2-2
Signal Acquisition System	2-3
Horizontal System	2-3
Trigger System	2-5
Acquisition Control	2-6
On-Board User Assistance	2-7
Measurement Assistance	2-7
Storage	2-8
I/O	2-8
Display	2-9
Nominal Traits	2-11
Warranted Characteristics	2-19
Typical Characteristics	2-27

List of Figures

Figure 1-1: Map of display functions	1-3
Figure 1-2: Verifying adjustments and signal-path compensation ..	1-6
Figure 1-3: Universal test hookup for functional tests – TDS 600B shown	1-8
Figure 1-4: Measurement of DC offset accuracy at zero setting	1-31
Figure 1-5: Initial test hookup	1-32
Figure 1-6: Measurement of DC accuracy at maximum offset and position	1-35
Figure 1-7: Initial test hookup	1-37
Figure 1-8: Optional initial test hookup	1-37
Figure 1-9: Measurement of analog bandwidth	1-40
Figure 1-10: Initial test hookup	1-42
Figure 1-11: Measurement of channel delay – TDS 684B shown	1-44
Figure 1-12: Initial test hookup	1-46
Figure 1-13: Measurement of accuracy – Long-term and delay time	1-48
Figure 1-14: Initial test hookup	1-50
Figure 1-15: Measurement of time accuracy for pulse and glitch triggering	1-51
Figure 1-16: Initial test hookup	1-53
Figure 1-17: Measurement of trigger-level accuracy	1-55
Figure 1-18: Initial test hookup	1-58
Figure 1-19: Measurement of trigger sensitivity – 50 MHz results shown on a TDS 684B screen	1-59
Figure 1-20: Initial test hookup	1-62
Figure 1-21: Measurement of main trigger out limits	1-64
Figure 1-22: Initial test hookup	1-66
Figure 1-23: Measurement of probe compensator frequency	1-68
Figure 1-24: Subsequent test hookup	1-69
Figure 1-25: Measurement of probe compensator amplitude	1-70
Figure 1-26: Jitter test hookup	1-72
Figure 1-27: Jitter test displayed waveform – TDS 684B shown	1-73
Figure 1-28: Jitter test when completed – TDS 684B shown	1-74
Figure 1-29: Triggered signal range test – 300 mV	1-75
Figure 1-30: Triggered signal range test – 75 mV	1-76
Figure 1-31: 60 Hz Rejection test hookup	1-77
Figure 1-32: 60 Hz Rejection test setup signal	1-77

Figure 1-33: Subsequent 60 Hz Rejection test hookup	1-78
Figure 1-34: 60 Hz Rejection test result – TDS 684B shown	1-79
Figure 1-35: Line count accuracy test hookup	1-80
Figure 1-36: Line count accuracy test setup waveform – TDS 684B shown	1-81
Figure 1-37: Line count accuracy correct result waveform	1-82
Figure 1-38: Setup for sync duty cycle test	1-84
Figure 1-39: Sync duty cycle test: one-div neg pulse waveform	1-85
Figure 1-40: Sync duty cycle test: critically adjusted pulse	1-86
Figure 1-41: Sine wave generator leveling equipment setup	1-88
Figure 1-42: Equipment setup for maximum amplitude	1-90
Figure 1-43: Reference-receiver performance-verification set up ...	1-93
Figure 1-44: Optical impulse of Ch1 input from OA5022 Optical Attenuator (OIG501 / OIG502 fed into optical attenuator in Step 1)	1-95
Figure 1-45: Optical impulse response for OC-12 SONET Reference Receiver	1-98
Figure 1-46: Optical impulse response for OC-12 SONET Reference Receiver	1-99

List of Tables

Table 1-1: Test equipment	1-16
Table 1-2: DC offset accuracy (zero setting)	1-30
Table 1-3: DC Voltage measurement accuracy	1-34
Table 1-4: Analog bandwidth	1-39
Table 1-5: Delay between channels worksheet	1-45
Table 1-6: Trigger level accuracy readout	1-54
Table 1-7: Delayed trigger level accuracy readout	1-56
Table 1-8: Available Filters	1-91
Table 1-9: Reference Receiver Filter Options:	1-91
Table 1-10: Option 3C and 4C Specifications	1-92
Table 1-11: Available receivers	1-92
Table 1-12: Bessel Thompson frequency response and reference receiver limits	1-100
Table 2-1: Key features of the TDS 500D, 600B and 700D oscilloscopes	2-1
Table 2-2: Record length and divisions per record vs. TDS model ..	2-4
Table 2-3: Nominal traits — Signal acquisition system	2-11
Table 2-4: Nominal traits — Time base system	2-12
Table 2-5: Nominal traits — Triggering system	2-13
Table 2-6: Nominal traits — Display system	2-15
Table 2-7: Nominal traits — GPIB interface, output ports, and power fuse	2-16
Table 2-8: Nominal traits — Data handling and reliability	2-16
Table 2-9: Nominal traits — Mechanical	2-17
Table 2-10: Warranted characteristics — Signal acquisition system	2-20
Table 2-11: Warranted characteristics — Time base system	2-21
Table 2-12: Warranted characteristics — Triggering system	2-22
Table 2-13: Warranted characteristics — Output ports, probe compensator, and power requirements	2-23
Table 2-14: Warranted characteristics — Environmental	2-24
Table 2-15: Certifications and compliances	2-26
Table 2-16: Typical characteristics — Signal acquisition system ...	2-27
Table 2-17: Typical characteristics — Triggering system	2-30