

型 名	社 名	f	最大定格 (Ta=25℃)				電 気 的 特 性 (Ta=25℃)																	外 形 備 考	
			V _{DS} or V _{DG}	V _{GS}	I _D * /CH	P _D * /CH	I _{GSS}		I _{BSS}		V _{GS(th)}		V _{DS} = V _{GS}	R _{DS(on)}			I _{D(on)}		g _{fs}		Ciss	Coss	Crss		V _{GS} =0
							(max)	V _{GS} (V)	(max)	V _{DS} (V)	min	max		(max) *typ	V _{GS} (V)	I _D (A)	(min) *typ	V _{GS} (S)	I _D (A)	(*typ) (max) (pF)	(*typ) (max) (pF)	(*typ) (max) (pF)			
(V)	(V)	(A)	(W)	(nA)	(V)	(μA)	(V)	(V)	(mA)	(Ω)	(V)	(A)	(A)	(V)	(S)	(A)	(pF)	(pF)	(pF)	(V)					
MTM6N60	MOT	N	600 ±20	6	150	500	20	250	510	2.0	4.5	1	1.2	10	3.0		2.0	3.0	1800	350	150	25	TO-204AA		
MTM6N85	MOT	N	850 ±20	6	150	±100	±20	200	850	2.0	4.5	1	3.0	10	3.0		2.0	3.0	2600	350	200	25	TO-204AA		
MTM6N90	MOT	N	900 ±20	6	150	±100	±20	200	900	2.0	4.5	1	3.0	10	3.0		2.0	3.0	2600	350	200	25	TO-204AA		
MTM7N12	MOT	N	120 ±20	7	75	500	20	250	96	2.0	4.5	1	0.7	10	3.5		1.5	3.5	400	175	30	25	TO-204AA		
MTM7N15	MOT	N	150 ±20	7	75	500	20	250	120	2.0	4.5	1	0.7	10	3.5		1.5	3.5	400	175	30	25	TO-204AA		
MTM7N18	MOT	N	180 ±20	7	75	500	20	250	153	2.0	4.5	1	0.7	10	3.5		1.5	3.5	700	300	80	25	TO-204AA		
MTM7N20	MOT	N	200 ±20	7	75	500	20	250	170	2.0	4.5	1	0.7	10	3.5		1.5	3.5	700	300	80	25	TO-204AA		
MTM7N45	MOT	N	450 ±20	7	150	500	20	250	383	2.0	4.5	1	0.8	10	3.5		2.0	3.5	1800	350	150	25	TO-204AA		
MTM7N50	MOT	N	500 ±20	7	150	500	20	250	425	2.0	4.5	1	0.8	10	3.5		2.0	3.5	1800	350	150	25	TO-204AA		
MTM8N08	MOT	N	80 ±20	8	75	500	20	250	68	2.0	4.5	1	0.5	10	4.0		1.5	4.0	400	350	100	25	TO-204AA		
MTM8N10	MOT	N	100 ±20	8	75	500	20	250	85	2.0	4.5	1	0.5	10	4.0		1.5	4.0	400	350	100	25	TO-204AA		
MTM8N12	MOT	N	120 ±20	8	75	500	20	250	102	2.0	4.5	1	0.5	10	4.0		2.0	4.0	700	300	80	25	TO-204AA		
MTM8N15	MOT	N	150 ±20	8	75	500	20	250	128	2.0	4.5	1	0.5	10	4.0		2.0	4.0	700	300	80	25	TO-204AA		
MTM8N18	MOT	N	180 ±20	8	75	500	20	250	153	2.0	4.5	1	0.4	10	4.0		3.0	4.0	1000	300	80	25	TO-204AA		
MTM8N20	MOT	N	200 ±20	8	75	500	20	250	170	2.0	4.5	1	0.4	10	4.0		3.0	4.0	1000	300	80	25	TO-204AA		
MTM8N35	MOT	N	350 ±20	8	150	500	20	250	298	2.0	4.5	1	0.55	10	4.0		3.0	4.0	1800	350	150	25	TO-204AA		
MTM8N40	MOT	N	400 ±20	8	150	500	20	250	340	2.0	4.5	1	0.55	10	4.0		3.0	4.0	1800	350	150	25	TO-204AA		
MTM8N60	MOT	N	600 ±20	8	150	±100	±20	200	600	2	4.5	1	0.5	10	4		4	4	2300	425	180	25	TO-204AA		
MTM8P08	MOT	P	-80 ±20	-8	75	-500	-20	-250	-68	-2.0	-4.5	-1	0.4	-10	-4.0		2.0	-4.0	1200	600	180	-25	TO-204AA		
MTM8P10	MOT	P	-100 ±20	-8	75	-500	-20	-250	-85	-2.0	-4.5	-1	0.4	-10	-4.0		2.0	-4.0	1200	600	180	-25	TO-204AA		
MTM8P18	MOT	P	180 ±20	8	125	±100	±20	10	180	2	4.5	1	0.7	10	4		2	4	1600	400	120	25	TO-204AA		
MTM8P20	MOT	P	200 ±20	8	125	±100	±20	10	200	2	4.5	1	0.7	10	4		2	4	1600	400	120	25	TO-204AA		
MTM8P25	MOT	P	-250 ±20	-8	75	±100	±20		-2.0	-4.5	-1	2.0	-10	-4.0		3.0	-4.0	2200	500	300	-25	TO-204AA			
MTM10N05	MOT	N	50 ±20	10	75	500	20	250	43	2.0	4.5	1	0.28	10	5.0		2.5	5.0	400	350	100	25	TO-204AA		
MTM10N06	MOT	N	60 ±20	10	75	500	20	250	52	2.0	4.5	1	0.28	10	5.0		2.5	5.0	400	350	100	25	TO-204AA		
MTM10N06E	MOT	N	60 ±20	10	75	±100	±20	10	60	2	4.5	1	0.2	10	5		3.8	5	600	350	100	25	TO-204AA		
MTM10N08	MOT	N	80 ±20	10	75	500	20	250	68	2.0	4.5	1	0.33	10	5.0		2.5	5.0	600	400	80	25	TO-204AA		
MTM10N10	MOT	N	100 ±20	10	75	500	20	250	85	2.0	4.5	1	0.33	10	5.0		2.5	5.0	600	400	80	25	TO-204AA		
MTM10N12	MOT	N	120 ±20	10	75	500	20	250	102	2.0	4.5	1	0.3	10	5.0		2.5	5.0	1200	500	120	25	TO-204AA		
MTM10N12L	MOT	N	120 ±15	10	75	±100	±15	1	120	1	2	1	0.3	5	5		4	5	1200	250	60	25	TO-204AA		

チャネルの * は Pch と Nch の両方が入っていることを表す。