



STPS20150CT/CG/CR/CFP

HIGH VOLTAGE POWER SCHOTTKY RECTIFIER

MAIN PRODUCT CHARACTERISTICS


$I_{F(AV)}$	2 x 10 A
V_{RRM}	150 V
T_j	175°C
$V_F (max)$	0.75 V

FEATURES AND BENEFITS

- HIGH JUNCTION TEMPERATURE CAPABILITY
- GOOD TRADE OFF BETWEEN LEAKAGE CURRENT AND FORWARD VOLTAGE DROP
- LOW LEAKAGE CURRENT
- AVALANCHE CAPABILITY SPECIFIED

DESCRIPTION

Dual center tap schottky rectifier designed for high frequency Switched Mode Power Supplies.



ABSOLUTE RATINGS (limiting values, per diode)

Symbol	Parameter				Value	Unit
V _{RRM}	Repetitive peak reverse voltage				150	V
I _{F(RMS)}	RMS forward current				30	A
I _{F(AV)}	Average forward current δ = 0.5	TO-220AB D ² PAK / I ² PAK	T _c = 155°C	Per diode	10	A
		TO-220FPAB	T _c = 135°C	Per device	20	
I _{FSM}	Surge non repetitive forward current		tp = 10 ms sinusoidal		180	A
P _{ARM}	Repetitive peak avalanche power		tp = 1μs T _j = 25°C		6700	W
T _{stg}	Storage temperature range				- 65 to + 175	°C
T _j	Maximum operating junction temperature				175	°C
dV/dt	Critical rate of rise of reverse voltage				10000	V/μs

THERMAL RESISTANCES

Symbol	Parameter			Value	Unit
$R_{th(j-c)}$	Junction to case	TO-220AB / D ² PAK / I ² PAK	Per diode	2.2	°C/W
		TO-220FPAB		4.5	
		TO-220AB / D ² PAK / I ² PAK	Total	1.3	
		TO-220FPAB		3.5	
$R_{th(c)}$		TO-220AB / D ² PAK / I ² PAK	Coupling	0.3	
		TO-220FPAB		2.5	

When the diodes 1 and 2 are used simultaneously :
 $\Delta T_j(\text{diode 1}) = P(\text{diode 1}) \times R_{th(j-c)}(\text{Per diode}) + P(\text{diode 2}) \times R_{th(c)}$

STATIC ELECTRICAL CHARACTERISTICS (per diode)

Symbol	Parameter	Tests conditions		Min.	Typ.	Max.	Unit
I_R^*	Reverse leakage current	$T_j = 25^\circ\text{C}$	$V_R = V_{RRM}$			5.0	μA
		$T_j = 125^\circ\text{C}$				5.0	mA
V_F^{**}	Forward voltage drop	$T_j = 25^\circ\text{C}$	$I_F = 10\text{ A}$			0.92	V
		$T_j = 125^\circ\text{C}$	$I_F = 10\text{ A}$		0.69	0.75	
		$T_j = 25^\circ\text{C}$	$I_F = 20\text{ A}$			1	
		$T_j = 125^\circ\text{C}$	$I_F = 20\text{ A}$		0.79	0.86	

Pulse test : * $t_p = 5\text{ ms}$, $\delta < 2\%$
 ** $t_p = 380\text{ }\mu\text{s}$, $\delta < 2\%$

To evaluate the conduction losses use the following equation:
 $P = 0.64 \times I_{F(AV)} + 0.011 I_{F(RMS)}^2$

Fig. 1: Average forward power dissipation versus average forward current (per diode).




Fig. 2: Average forward current versus ambient temperature ($\delta = 0.5$, per diode).




Fig. 3: Normalized avalanche power derating versus pulse duration.




Fig. 4: Normalized avalanche power derating versus junction temperature.




Fig. 5-1: Non repetitive surge peak forward current versus overload duration (maximum values, per diode). TO-220AB, I²PAK and D²PAK




Fig. 5-2: Non repetitive surge peak forward current versus overload duration (maximum values, per diode). TO-220FPAB




Fig. 6-1: Relative variation of thermal impedance junction to case versus pulse duration. TO-220AB, I²PAK and D²PAK




Fig. 6-2: Relative variation of thermal impedance junction to case versus pulse duration. TO-220FPAB




Fig. 7: Reverse leakage current versus reverse voltage applied (typical values, per diode).




Fig. 8: Junction capacitance versus reverse voltage applied (typical values, per diode).




Fig. 8: Forward voltage drop versus forward current (per diode).







Fig. 9: Thermal resistance junction to ambient versus copper surface under tab (Epoxy printed circuit board, Cu = 35μm) (STPS20150CG only).




PACKAGE MECHANICAL DATA **D²PAK**




FOOT PRINT DIMENSIONS (in millimeters)




PACKAGE MECHANICAL DATA
TO-220AB



PACKAGE MECHANICAL DATA
I²PAK



PACKAGE MECHANICAL DATA
TO-220FPAB

OTHER INFORMATION

Ordering type	Marking	Package	Weight	Base qty	Delivery mode
STPS20150CT	STPS20150CT	TO-220AB	2.20 g	50	Tube
STPS20150CG	STPS20150CG	D ² PAK	1.48 g	50	Tube
STPS20150CG-TR	STPS20150CG	D ² PAK	1.48 g	1000	Tape & Reel
STPS20150CR	STPS20150CR	I ² PAK	1.49 g	50	Tube
STPS20150CFP	STPS20150CFP	TO-220FPAB	2.0 g	50	Tube

■ EPOXY MEETS UL94,V0

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 2003 STMicroelectronics - Printed in Italy - All rights reserved.

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - Finland - France - Germany
 Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore
 Spain - Sweden - Switzerland - United Kingdom - United States.



<http://www.st.com>