



element14

EN - For pricing and availability in your local country please visit one of the below links:

DE - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

[ACPL-214-500E](#)

[ACPL-214-500E](#)

EN

This Datasheet is presented by
the manufacturer

DE

Dieses Datenblatt wird vom
Hersteller bereitgestellt

FR

Cette fiche technique est
présentée par le fabricant

AC Input, Half-Pitch Phototransistor Optocoupler


Data Sheet

Description

The ACPL-214 is an AC-input single channel half-pitch phototransistor optocoupler that contains two light-emitting diodes connected inversely parallel and optically coupled to a phototransistor. It is packaged in a 4-pin SO package.

The input-output isolation voltage is rated at 3000 Vrms. Response time, t_r , is 2 μ s typically, while minimum CTR is 20 percent at input current of 1 mA.

ACPL-214 Pin Layout



Pin 1	Anode
Pin 2	Cathode
Pin 3	Emitter
Pin 4	Collector

Features

- Current transfer ratio
(CTR: 20% (min) at $I_F = \pm 1$ mA, $V_{CC} = 5$ V)
- High input-output isolation voltage
($V_{ISO} = 3000 V_{RMS}$)
- Non-saturated response time
(t_r : 2 μ s (typ) at $V_{CC} = 10$ V, $I_C = 2$ mA, $R_L = 100 \Omega$)
- SO package
- CMR 10 kV/ μ s (typical)
- Safety and regulatory approvals
 - cUL
 - IEC/EN/DIN EN 60747-5-5
- Options available:
 - CTR Ranks 0, A

Applications

- I/O Interface for programmable controllers, computers
- Sequence controllers
- System appliances, measuring instruments
- Signal transmission between circuits of different potentials and impedances.

Ordering Information

ACPL-214-xxxx is UL Recognized with 3000 Vrms for 1 minute per UL1577 and Canadian Component Acceptance Notice #5.

Part Number	RoHS Compliant Option		Package	Surface Mount	Tape and Reel	IC Orientation	IEC/EN/DIN EN 60747-5-5	Quantity
	Rank '0' 20%<CTR<400% $I_F=\pm 1\text{ mA}$, $V_{CE}=5V$	Rank 'A' 50%<CTR<250% $I_F=\pm 1\text{ mA}$, $V_{CE}=5V$						
ACPL-214	-500E	-50AE	SO-4	X	X	0°		3000 pcs per reel
	-560E	-56AE	SO-4	X	X	0°	X	3000 pcs per reel
	-700E	-70AE	SO-4	X	X	180°		3000 pcs per reel
	-760E	-76AE	SO-4	X	X	180°	X	3000 pcs per reel

To order, choose a part number from the part number column and combine with the desired option from the option column to form an order entry.

Example 1:


ACPL-214-560E to order product of SO-4 Surface Mount package in Tape and Reel packaging with IEC/EN/DIN EN 60767-5-5 Safety Approval, 20% < CTR < 400% and RoHS compliant.

Example 2:

ACPL-214-50AE to order product of SO-4 Surface Mount package in Tape and Reel packaging with 50% < CTR < 250% and RoHS compliant.

Option datasheets are available. Contact your Broadcom sales representative or authorized distributor for information.

Package Outline Drawings



Solder Reflow Temperature Profile

Recommended reflow condition as per JEDEC Standard, J-STD-020 (latest revision). Non-Halide Flux should be used.

Absolute Maximum Ratings

Parameter	Symbol	ACPL-214	Units	Note
Storage Temperature	T_S	-55~125	°C	
Operating Temperature	T_A	-55~110	°C	
Average Forward Current	$I_{F(AVG)}$	±50	mA	
Pulse Forward Current	I_{FSM}	±1	A	
LED Power Dissipation	P_I	65	mW	
Collector Current	I_C	50	mA	
Collector-Emitter Voltage	V_{CEO}	80	V	
Emitter-Collector Voltage	V_{ECO}	7	V	
Isolation Voltage (AC for 1 minute, R.H. 40%~60%)	V_{ISO}	3000	V_{RMS}	1 minute
Collector Power Dissipation	P_C	150	mW	
Total Power Dissipation	P_{TOT}	200	mW	
Lead Solder Temperature	260°C for 10 seconds			

Electrical Specifications

Over recommended ambient temperature at 25°C unless otherwise specified.

Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions	Note
Forward Voltage	V_F	—	1.2	1.4	V	$I_F = \pm 20 \text{ mA}$	Figure 6
Terminal Capacitance	C_t	—	60	—	pF	$V = 0, f = 1 \text{ MHz}$	
Collector Dark Current	I_{CEO}	—	—	100	nA	$V_{CE} = 48\text{V}, I_F = 0 \text{ mA}$	Figure 12
Collector-Emitter Breakdown Voltage	BV_{CEO}	80	—	—	V	$I_C = 0.5 \text{ mA}, I_F = 0 \text{ mA}$	
Emitter-Collector Breakdown Voltage	BV_{ECO}	7	—	—	V	$I_E = 100 \mu\text{A}, I_F = 0 \text{ mA}$	
Current Transfer Ratio	CTR	20	—	400	%	$I_F = \pm 1 \text{ mA}, V_{CE} = 5\text{V}$	$CTR = (I_C / I_F) \times 100\%$
Saturated CTR	$CTR_{(sat)}$	—	100	—	%	$I_F = \pm 1 \text{ mA}, V_{CE} = 0.4\text{V}$	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	—	—	0.4	V	$I_F = \pm 8 \text{ mA}, I_C = 2.4 \text{ mA}$	Figure 14
Isolation Resistance	R_{iso}	5×10^{10}	1×10^{11}	—	Ω	DC500V, R.H. 40%~60%	
Floating Capacitance	C_F	—	0.8	1	pF	$V = 0, f = 1 \text{ MHz}$	
Cut-off Frequency (–3dB)	F_C	—	80	—	kHz	$V_{CC} = 5\text{V}, I_C = 2 \text{ mA},$ $R_L = 100\Omega$	Figure 2, Figure 19
Response Time (Rise)	t_r	—	2	—	μs	$V_{CC} = 10\text{V}, I_C = 2 \text{ mA},$ $R_L = 100\Omega$	Figure 1
Response Time (Fall)	t_f	—	3	—	μs		
Turn-on Time	t_{on}	—	3	—	μs		
Turn-off Time	t_{off}	—	3	—	μs		
Turn-ON Time	t_{ON}	—	2	—	μs	$V_{CC} = 5\text{V}, I_F = 16 \text{ mA},$ $R_L = 1.9 \text{ k}\Omega$	Figure 1, Figure 17
Storage Time	T_S	—	25	—	μs		
Turn-OFF Time	t_{OFF}	—	40	—	μs		
Common Mode Rejection Voltage	CMR	—	10	—	kV/ μs	$T_a = 25^\circ\text{C}, R_L = 470\Omega,$ $V_{CM} = 1.5 \text{ kV(peak)},$ $I_F = 0 \text{ mA}, V_{CC} = 9\text{V},$ $V_{np} = 100 \text{ mV}$	Figure 20

Figure 1 Switching Time Test Circuit




Figure 2 Frequency Response Test Circuit










Figure 3 Forward Current vs. Ambient Temperature**Figure 4 Collector Power Dissipation vs. Ambient Temperature****Figure 5 Pulse Forward Current vs. Duty Cycle Ratio****Figure 6 Forward Current vs. Forward Voltage****Figure 7 Forward Voltage Temperature Coefficient vs. Forward Current****Figure 8 Pulse Forward Current vs. Pulse Forward Voltage**

Figure 9 Collector Current vs. Collector-Emitter Voltage




Figure 10 Collector Current vs. Small Collector-Emitter Voltage




Figure 11 Collector Current vs. Forward Current




Figure 12 Collector Dark Current vs. Ambient Temperature




Figure 13 Current Transfer Ratio vs. Forward Current




Figure 14 Collector-Emitter Saturation Voltage vs. Ambient Temperature




Figure 15 Collector Current vs. Ambient Temperature




Figure 16 Switching Time vs. Load Resistance




Figure 17 Switching Time vs. Ambient Temperature




Figure 18 Collector-Emitter Saturation Voltage vs. Forward Current




Figure 19 Frequency Response





Figure 20 CMR Test Circuit



For product information and a complete list of distributors, please go to our web site: www.broadcom.com.

Broadcom, the pulse logo, Connecting everything, Avago Technologies, Avago, and the A logo are among the trademarks of Broadcom and/or its affiliates in the United States, certain other countries and/or the EU.

Copyright © 2011–2017 by Broadcom. All Rights Reserved.

The term "Broadcom" refers to Broadcom Limited and/or its subsidiaries. For more information, please visit www.broadcom.com.

Broadcom reserves the right to make changes without further notice to any products or data herein to improve reliability, function, or design.

Information furnished by Broadcom is believed to be accurate and reliable. However, Broadcom does not assume any liability arising out of the application or use of this information, nor the application or use of any product or circuit described herein, neither does it convey any license under its patent rights nor the rights of others.

AV02-0469EN – April 26, 2017





element14

EN - For pricing and availability in your local country please visit one of the below links:

DE - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

[ACPL-214-500E](#)

[ACPL-214-500E](#)

EN

This Datasheet is presented by
the manufacturer

DE

Dieses Datenblatt wird vom
Hersteller bereitgestellt

FR

Cette fiche technique est
présentée par le fabricant