


Distribution components with F connectors

5-862MHz

2, 3 and 4 way splitters



► PAS12(X)2011


PAS12(X)2011

Item	Code	Insertion loss dB			Isolation between outputs dB			Dimensions mm	Weight g
		5-40 MHz	40-470 MHz	470-862 MHz	5-40 MHz	40-470 MHz	470-862 MHz		
PAS1222011, 2 out.	PAS1222011	3.4 ± 0.3	3.4 ± 0.3	3.6 ± 0.4	16	22	20	53x50x25	55
PAS1232011, 3 out.	PAS1232011	5.3 ± 0.3	5.3 ± 0.3	5.6 ± 0.5	16	20	18	74x50x25	76
PAS1242011, 4 out.	PAS1242011	7.2 ± 0.3	7.2 ± 0.3	7.5 ± 0.5	18	20	6	74x50x25	8

Distribution components with F connectors

5-862MHz

1, 2, 4, 6 and 8 way taps



► PAS2222(X)11



► PAS2242(X)11



► PAS2212(X)11



► PAS22(X)2811

PAS2212(X)11 - 1 WAY TAPS

Item	Code	Tap loss dB			Isolation loss dB			Output-tap isolation dB		
		5-40 MHz	40-470 MHz	470-862 MHz	5-40 MHz	40-470 MHz	470-862 MHz	5-40 MHz	40-470 MHz	470-862 MHz
PAS2212111	PAS2212111	8.5 ± 1	8.5 ± 1	8.5 ± 1	1.6 ± 0.2	1.6 ± 0.2	2 ± 0.3	22	20	18
PAS2212211	PAS2212211	12.5 ± 1	12.5 ± 1	12.5 ± 1	0.7 ± 0.2	0.7 ± 0.2	0.8 ± 0.3	26	26	16
PAS2212311	PAS2212311	16 ± 1	16 ± 1	16 ± 1	0.5 ± 0.2	0.5 ± 0.2	0.6 ± 0.3	28	26	26
PAS2212411	PAS2212411	20 ± 1	20 ± 1	20 ± 1	0.5 ± 0.2	0.5 ± 0.2	0.6 ± 0.3	30	30	26
PAS2212511	PAS2212511	24 ± 1	24 ± 1	24 ± 1	0.5 ± 0.2	0.5 ± 0.2	0.6 ± 0.3	32	32	28

Splitters and taps

PAS2222(X)11 - 2 WAY TAPS

Item	Code	Tap loss dB			Isolation loss dB			Output-tap isolation dB		
		5-40 MHz	40-470 MHz	470-862 MHz	5-40 MHz	40-470 MHz	470-862 MHz	5-40 MHz	40-470 MHz	470-862 MHz
PAS2222111	PAS2222111	8.5 ± 1	8.5 ± 1	8.5 ± 1	3.4 ± 0.5	3.6 ± 0.5	3.8 ± 0.5	22	20	16
PAS2222211	PAS2222111	12.5 ± 1	12.5 ± 1	12.5 ± 1	1.2 ± 0.3	1.2 ± 0.3	1.2 ± 0.4	26	24	22
PAS2222311	PAS2222311	16 ± 1	16 ± 1	16 ± 1	1.2 ± 0.3	1.2 ± 0.3	1.5 ± 0.4	28	24	22
PAS2222411	PAS2222411	20 ± 1	20 ± 1	20 ± 1	0.5 ± 0.2	0.5 ± 0.2	0.6 ± 0.3	30	28	26
PAS2222511	PAS2222511	24 ± 1	24 ± 1	24 ± 1	0.5 ± 0.2	0.5 ± 0.2	0.6 ± 0.3	30	30	30
PAS2222611	PAS2222611	27 ± 1	27 ± 1	27 ± 1	0.5 ± 0.2	0.5 ± 0.2	0.6 ± 0.3	30	30	30

PAS2242(X)11 - 4 WAY TAPS

Item	Code	Tap loss dB		Isolation loss dB	Output-tap isolation dB		
		5-862 MHz		5-862 MHz	5-40MHz	40-470 MHz	470-862 MHz
		Tap 1 & 2	Tap 3 & 4				
PAS2242211	PAS2242211	12 ± 1	13 ± 1	4.5 ± 1	26	26	22
PAS2242311	PAS2242311	16 ± 1	17 ± 1	2.5 ± 1	26	26	22
PAS2242411	PAS2242411	20 ± 1	21 ± 1	2.5 ± 1	30	30	26
PAS2242511	PAS2242511	24 ± 1	25 ± 1	2.5 ± 1	30	30	28

PAS2242(X)11 - 4 WAY TAPS

Item	Code		Tap loss dB			Isolation loss dB	Output-tap isolation dB		
			5-40 MHz	40-470 MHz	470-862 MHz		5-40 MHz	40-470 MHz	470-862 MHz
PAS2242811 4 channels	PAS2242811	Tap 1	12.5 ± 1	12.5 ± 1	12.5 ± 1	4 ± 1	27	26	24
		Tap 2	13.5 ± 1.5	13.5 ± 1.5	13.5 ± 1.5				
		Tap 3	14.5 ± 1.5	14.5 ± 1.5	14.5 ± 1.5				
		Tap 4	15.5 ± 1.5	15.5 ± 1.5	15.5 ± 1.5				
PAS2262811 6 channels	PAS2262811	Tap 5	17 ± 1.5	17 ± 1	17 ± 1	6 ± 1	27	26	24
		Tap 6	13.5 ± 1.5	13.5 ± 1.5	13.5 ± 1.5				
PAS2282811 8 channels	PAS2282811	Tap 7	19 ± 1.5	19 ± 1	19 ± 1	8 ± 1	27	26	24
		Tap 8	19.5 ± 1.5	19.5 ± 1.5	19.5 ± 1.5				